

Server Cabinets

Fixed Wall Mounted

RCK-SH-05FF-4UWB	4U wall box 600x450, 1 fixed shelf, no fan
RCK-SH-05FF-6UWB	6U wall box, 600x450, 1 fan, 1 fixed shelf
RCK-SH-05FF-9UWB	9U wall box, 600x450, 1 fan, 1 fixed shelf
RCK-SH-05FF-12UWB	12U wall box, 600x450, 1 fan, 1 fixed shelf



Features

- Includes fixed shelf & fan kit
- Max loading: 30 kg
- Quick open side doors, easy to install and maintain
- RU markings on front & rear mounting rails
- Top and bottom wire path
- Wall or Floor installation type
- Convenient and quick wall mounting
- Lockable via keys
- Supplied complete, no assembly required
- Gloss black colour, easy clean surface
- Material: SPCC quality cold rolled steel
- Thickness: Square hole strips 1.2mm, others 1.0mm
- Surface Finish: Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting, powder-coated.
- Complies with ANSI/EIA RS-310-D,
- IEC297-2, DIN41491; PART1, DIN41494; PART7, GB/T3047.2-92 Compatible with 19" international standard and metrical standard & ETSI standards.

Swing Mounted

RCK-SH-02BC-6USF	6U wall box SF, 600x550, 1 fixed shelf, 1 fan
RCK-SH-02BC-6USF-600	6U wall box SF, 600x600, 1 fixed shelf, 1 fan
RCK-SH-02BC-9USF	9U wall box SF, 600x550, 1 fixed shelf, 1 fan
RCK-SH-02BC-12USF	12U wall box SF, 600x550, 1 fixed shelf, 1 fan
RCK-SH-02BC-18USF	18U wall box SF, 600x550, 1 fixed shelf, 1 fan



Features

- Includes fixed shelf & fan kit
- Max loading: 30 kg
- Quick open side doors for easy install and maintenance
- RU markings printed on both front & rear mounting rails
- Back entry, Top and bottom wire path
- Wall installation type
- Lockable via keys
- Supplied complete, no assembly required
- Gloss black colour
- Easy clean surface
- Venting on front and sides
- Material: SPCC quality cold rolled steel
- Thickness: Square hole strips 2.0mm, others 1.2mm
- Surface Finish: Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting, powder-coated.
- Complies with ANSI/EIA RS-310-D,
- IEC297-2, DIN41491; PART1, DIN41494; PART7, GB/T3047.2-92 standards.



19" Server & Network Cabinets



Floor-standing

RCK-SH-02BC-18U-800M	18U 600x800, Glass Front Door, 1 Shelf, 2 Fans
RCK-SH-05J-27U-600D	27U 600x600, Glass Front Door, 2 Shelves, 4 Fans <i>(Mesh Door Optional)</i>
RCK-SH-05J-27U-1000D	27U 600x1000, Glass Front Door, 2 Shelves, 4 Fans <i>(Mesh Door Optional)</i>
RCK-SH-05A-37U	37U 600x800, Glass Front Door, 2 Shelves, 4 Fans
RCK-SH05J-37U-1000M	37U 600x1000, Glass Front Door, 3 Fixed Shelves, 4 Fans
RCK-SH-05A-42U-600D	42U 600x1000(D), Mesh Door, 3 Fixed Shelf, 4 Fans <i>(Glass Door Optional)</i>

Features

- Includes fixed shelf & fan kit
- Max loading: 60kg
- Quick open side doors for easy install and maintenance
- RU markings printed on both front & rear mounting rails
- Back entry, Top and bottom wire path
- Wall installation type
- Lockable via keys
- Gloss black colour
- Easy clean surface
- Venting on front and sides
- Material: SPCC quality cold rolled steel
- Thickness: Square hole strips 2.0mm, Others 1.2mm
- Surface Finish: Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting, powder-coated.
- Complies with ANSI/EIA RS-310-D,
- IEC297-2, DIN41491; PART1, DIN41494; PART7, GB/T3047.2-92 standards.

