

*Solutions*



## A Versatile Bundling & Protection Solution

The **FLEXO PET (PTN)** grade is used in electronics, automotive, marine, and industrial wire harnessing applications where cost efficiency and durability are critical.

- Economical and Easy to Install
- Cut and Abrasion Resistant
- Expands up to 150%
- Halogen Free
- Resists Petrol, Engine Chemicals and Cleaning Solvents
- FMVSS 302 Approved

1m Lengths:

**6.4mm Nominal Size, 3.2/11.1mm Min/Max Thick**

Colours: Checkered Flag, Neon Red, Yellow or Blue

**38.1mm Nominal Size, 25.4/54mm Min/Max Thick**

Colour: Black




PTN0.25CF, PTN0.25NR,  
PTN0.25YL, PTN0.25BL,  
PTN1.50BK

## The Ultimate Termination Solution for FLEXO PET 38.1mm Sleeving

**Flexo Mounting System (FMS)** has been created to attractively terminate applications with a secure mountable end.



Easy Field Installation



Universal Screw Mount



Flexo Mounting Wall Plate & Flange



FMS1.50FKBK



Easy Clip, No Special Tool Required



Fits in Single Gang Wall Box



Flexo Flange - Pack of 5

## Flexible, Semi-Rigid Wrappable Split Braided Tube

**FLEXO F6's (F6N)** unique split, semi-rigid braided construction makes it the ideal solution for situations where ease of installation is of primary importance.

- Easy, Cost Effective Installation
- 25% Edge Overlap
- Cut and Abrasion Resistant
- Halogen Free
- Retains Shape & Rigidity
- Melt Temp 250°C

1m Lengths:

**12.7mm Nominal Size, 0.6mm Wall Thickness**

Colours: Black, Orange, Platinum Gray

**31.8mm Nominal Size, 1mm Wall Thickness**

Colour: Black



F6N0.50BK, F6N0.50OR,  
F6N0.50PG, F6N1.25BK

## Woven, Split Tubular Harness Wrap

**F6 WOVEN WRAP (F6W)** utilizes a unique blend of monofilament and multifilament polyester fibers, providing superior elastic flexibility with unbeatable coverage over any harness assembly.

- High Coverage
- Easy, Cost Effective Installation
- More Flexible than Split Convuluted or Spiral Wrap

1m Lengths:

**25.4mm Nominal Size, 0.7mm Wall Thickness**

Colour: Black

**50.8mm Nominal Size, 0.7mm Wall Thickness**

Colour: Black



F6W1.00BK, F6W2.00BK

## Adjustable Diameter Sleeve with Easy On, Easy Off Access

**GRIP WRAP (GWN)** is a lightweight, abrasion resistant sleeving with a unique hook sealing system that eliminates spot taping and does not require an open end for installation.

- Wrappable Design for Easy Installation and Removal
- Excellent Protection Against Cut-Through, Abrasion and Impact
- Closure Maintains Low Profile for Flat Cables & Harnesses

1m Lengths:

**34.9mm Nominal Size, 134.9mm Flat Width**

Colour: Black



GWN1-38BK

## The Latest Innovation Against Pesky Rodents!

**FLEXO RODENT RESISTANT (RRN)** is the latest solution from Techflex for fighting the harmful effects of unprotected wires which are exposed to rodents.

- Rodent Resistant
- Expands up to 150%
- Economical and Easy to Install
- Cut and Abrasion Resistant

1m Lengths:

**31.8mm Nominal Size**

Colour: Dark Brown



RRN1.25DB



## 2:1 Fabric Heatshrink Tubing

**SHRINKFLEX** Shrinks to ½ its original diameter. The woven construction makes this product extremely flexible and resistant to trapping water, heat and humidity.

- Shrink Temp. 135°C
- Highly Flexible
- Resists Common Automotive Chemicals
- Easily Installs Over Connectors & Splices
- Halogen Free

1m Lengths:

**12mm/6mm Unshrunk/Shrunk Diameter**

Colour: Black

**40mm/20mm Unshrunk/Shrunk Diameter**

Colour: Black



H2F0.48BK, H2F1.58BK

## Stylish Fluid Protection for Wires & Cables

**L6 LIQUID WRAP (L6N)** semi-rigid wraparound sleeving is engineered from tough braided polyester, and laminated with a layer of strong Mylar® sheeting.

- Water Repellent when Properly Sealed
- Will Not Support Growth of Bacteria
- Disinfects Easily
- Adhesive Resists Most Cleaners and Disinfectants

2.4m Lengths:

**25.4mm Nominal Size, 1.2mm Wall Thickness**

Colour: Black



L6N1.00BK